



# Revisions

## Revision B - (26th April 2011)

Tolerances added for 3 decimal places, existing conversion made from MM to Inches.

Added Post height (bottom of insulator to bottom of the Post)  
0.024 (0.60).

Insulation Resistance was 1000M $\Omega$ , now 500M $\Omega$

Contact Resistance was 40m $\Omega$ , now 30m $\Omega$

Products cut to specific sizes are uncancelable/nonreturnable

Parts are subject to change without notice

FPSR8-1 SERIES

.0315cl Dual Row - Right Angle  
Surface Mount Board to Board Socket

05 JUN 09

Scale  
NTS

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS IN INCHES (MM)  
TOLERANCES ARE:

ONE PLACE DECIMALS  $\pm 0.12$   
TWO PLACE DECIMALS  $\pm 0.06$   
THREE PLACE DECIMALS  $\pm 0.04$



4235 Earnings Way, New Albany, Indiana, 47150, USA  
1-800-782-3486 (USA/Canada/Mexico)

Tel: 812-944-7244  
Fax: 812-944-7268

E-mail: [mle@mlelectronics.com](mailto:mle@mlelectronics.com)  
Web: [www.mlelectronics.com](http://www.mlelectronics.com)

Revision  
B

Sheet  
2/2