

Revisions

Revision E - (16th Dec 2011)

Alignment Pin option added.

Revision D - (8th Dec 2012)

Plating options amended.

Removed:

H: 30 μ Gold on Contact Area / Matte Tin on Tail

G: 10 μ Gold on Contact Area / Flash on Tail

Added:

F: Gold Flash Over Entire Pin

Revision C - (19th Apr 2010)

Change to Specification; From 0.5 Ampere to 1.0 Ampere.

Revision B - (20th Mar 2008)

Amendment to packing options in ordering grid.

Revision A

TR-P = Tape and Reel with Plastic Pick and Place pad

TR-M = Tape and Reel with Metal Pick and Place pad

TR-K = Tape and Reel with Kapton Tape Pick and Place pad

TB-P = Tube with Plastic Pick and Place pad

TB-M = Tube with Metal Pick and Place pad

TB-K = Tube with Kapton Tape Pick and Place pad

TB-0 = Tube without Pick and Place Pad

BK-0 = Bulk without Pick and Place Pad

Revision B

TR-P = Tape and Reel with Plastic Pick and Place pad

TB-P = Tube with Plastic Pick and Place pad

TB-0 = Tube without Pick and Place Pad

If left blank, packaging at MLE's discretion

Pad may be metal, mylar or plastic

TSHSM-7-DV SERIES

.039 cl Dual Row - Surface Mount
Terminal Strip Headers - Vertical

06 MAR 07

Scale
NTS

UNLESS OTHERWISE SPECIFIED
DIMENSIONS IN INCHES (MM)
TOLERANCES ARE:

ONE PLACE DECIMALS \pm .100

TWO PLACE DECIMALS \pm .010

THREE PLACE DECIMALS \pm .005

FOUR PLACE DECIMALS \pm .0020

ANGLES
30°



4235 Earnings Way, New Albany, Indiana, 47150, USA
1-800-782-3486 (USA/Canada/Mexico)

Tel: 812-944-7244

Fax: 812-944-7268

E-mail: mle@mlelectronics.com

Web: www.mlelectronics.com

Revision
E

Sheet
2/2